

# 9110 AG-PROBE TR



## - THE FACTS -

If you are looking for an efficient and precise way to analyze your agricultural soil anywhere from 0 to 8 ft., then the 9110 Ag-Probe TR is the answer. Carbon bulk sampling can also be performed up to 1 meters or more!

The 9110 Ag-Probe TR is specifically designed for users who already own a tractor that can support the system. And, if you don't already own a tractor, this system can be purchased as a complete package. Powered by a tractor's power take-off (PTO) stub shaft, the 9110 Ag-Probe TR can reach deeper depths in almost any type of soil condition presented. It is important to note that sampling depths are contingent on the present soil conditions.

9110 Ag-Probes have a variety of tooling options available ranging in sampling diameters of 1.5 to 3 inches. This system is the reliable solution you've been searching for when it comes to reaching deeper depths for agricultural soil assessments.



Agricultural  
Geotechnical  
Environmental  
Groundwater

105 Harrison St.  
American Falls, ID 83211

Toll Free: 800.635.7330  
Office: 208.226.2017

ams@ams-samplers.com

facebook.com/amssampling

instagram.com/aminc/

linkedin.com/company/ams-inc/

youtube.com/@amssamplersusa

ams-samplers.com



# DIMENSIONS

- Weight: 1,040 lbs
- Overall length: 52.5 in
- Overall width: 43 in
- Overall height (folded): Carrier dependent
- Overall height (extended): 133 in

# MAST & PROBE

- Down force: 10,603 lbs
- Retraction force: 14,137 lbs
- Head travel rate up: 12 sec
- Head travel rate down: 9 sec
- Probe stroke: 60 in
- Standard hammer: 90 ft/lb
- Foot cylinder stroke: 16 in

# 9110 AG-PROBE TR FEATURES

- Fuel tank: Carrier dependent
- Horsepower: Carrier dependent
- Hydraulic flow rate: 9-10 gpm
- Hydraulic oil capacity: 6.8 gal
- Hydraulic oil pressure: 2,000 psi
- Hydraulic cooler: 11,000 btu

*Equipping the World to  
Sample the Earth  
Since 1942*

#### Customer Service:

Everyone at AMS is dedicated to exceeding our customer's needs and expectations. From answering questions about availability, proper use and care, and developing customized products, we're here to help!

*Call 208.226.2017 or 800.635.7330 for more info.*

